

5043 Farlin Ave. St. Louis, MO 63115 www.associatedequip.com 314-385-5178

60 Amp / 270 Amp Boost Wheel Smart Charger & Power Supply for Standard Automotive, Deep-Cycle, AGM and Gel Cell batteries, 220VAC

Product Bulletin

MODELS 6508A & 6508X

6508A w/EURO Plug

6508X w/Type I Plug





Specifications:

Model Number	6508A & 6508X
DC Output	60 Amps/70 Amps in Power Supply Mode
DC Leads	6 ½' 4 AWG
Clamp Rating	400A
Shipping Dimensions	17"x16"x30"
Weight	49 LBS
AC Cord / Voltage	6' 16-3 / 220VAC 50/60 Hz
Battery Types	12 Volt Flooded, AGM, and Gel Cell batteries - including Spiral Cell, Orbital TM or Optima TM Batteries
Display	Analog Meter and 3 LED display indicating charge status

Features:

- Electrical Stability System (ESS™) Technology turns 6508A & 6508X into a Stable Power Supply for Extended Service Procedures or Reflashes. Nominal 13.9V DC Output
- Program for Deep Discharge Recovery of Flooded Batteries
- Patented Diagnostics indicate Weak or Defective Battery
- Charges all types of 12 Volt Batteries
- 6508A with EURO plug
- 6508X for China Type I Plug
- Designed for AGM, Gel Cell, Sealed and Standard Flooded batteries including Spiral Cell, Orbital[™] or Optima[™] Batteries
- Dead Battery Override Control
- "Safe In Any Weather" Operation
- MADE IN USA