

M-3200UP-PLUS

M-3200UP-PLUS Laser



**Industry best Full
Featured space saving
Balancer
Accuracy, Speed,
Versatility in a space-
saving cabinet**



Shown with optional
3rd parameter
entry sonar sensor

Professional Wheel Service equipment manufactured by



Distributed and Supported Exclusively by the members of The Automotive Distributions Group, Inc.

www.ADGEquipment.com | 800-497-0009

'Wide Ranging Diverse Software Programs Improves Balancer Versatility

Advanced Software for handling any wheel, any weight placement quickly and easily

RPA WHEEL POSITIONING



RPA WHEEL POSITIONING

Balancer automatically rotates the wheel to the weight application position and electronically brakes and holds the wheel for fast/easy/accurate weight application every time.

HIDDEN WEIGHT SPOKE

Ideal for tape-on weight applications for spoke wheels. Software calculates the inside weight amount and then automatically splits the weight and guides the operator on placement of the weights behind the spokes for the most aesthetically pleasing balance job.

AUTO SELECT



AUTO SELECT

Balancer automatically selects the most appropriate ALU weight placement application for the wheel you are working on. Eliminates the need for operator selection of the right ALU program

OPT FLASH

Calculates the best position of Tire relative to the Wheel to minimize required balancing weight, creating the optimal vibration free ride with the least amount of balancing weight applied.

BALANCER CALIBRATION

Standard software program and factory calibration fixture allows the operator to calibrate balancer to factory specifications eliminating the need for a service call.



BALANCER CALIBRATION

ADVANCED HARDWARE FEATURES



LASER WEIGHT PLACEMENT

LASER WEIGHT PLACEMENT (Standard on M-3200UP-PLUS LASER)

On inside pare weight applications balancer automatically activates cabinet mounted Red Laser line to accurately spot exact weight position calculated. Eliminates all guess work on difficult tape weight applications.



WHITE LED WHEEL ILLUMINATION

WHITE LED WHEEL ILLUMINATION

To aid in cleaning wheel and weight application a white LED lighting array automatically illuminate the inside of the wheel for tape weight applications.

40mm INDUSTRIAL HARDENED SHAFT

Zero deflection hardened shaft for years of maintenance free balancing accuracy



40mm INDUSTRIAL HARDENED SHAFT

CAPTURED BACK SPRING

To insure rear cone mounting and eliminate spring misplacement and work area clutter, the spring is encapsulated on the balancer shaft



SPEED NUT

SPEED NUT

Durable high impact polymer speed nut saves time on both mounting and demounting every wheel, reducing R&R time.



2D DATA ENTRY ARM

2D DATA ENTRY ARM

Touch & Go parameter entry arm. Simply touch the arm to the wheel and both Distance out and Wheel diameter are entered

SONAR THIRD PARAMETER ENTRY

(standard on 3D models)

Patented sonar sensor mounted to the balancer hood automatically enters the third parameter (wheel width) when hood is lowered. Fastest parameter entry system in the industry



SONAR THIRD PARAMETER ENTRY

STANDARD ACCESSORIES



- Wheel Width Calipers
- Calibration Figure
- Four Hardened Centering Cones
- Removable 40mm Balancer Shaft
- Three Soft Speed Nut Cup Covers
- Speed Nut Cup Cover
- Snap On Front Cone Ring
- Speed Nut
- Wheel Weight Hammer/tool

Technical Specifications

Balancing Speed		90 to 130 rpm
Imbalance Resolution		1 g (.0353 oz)
Shaft diameter		40mm (1.57")
Centering Cone dimensions	Cone 1	1.63" – 2.515"
	Cone 2	2.106" – 3.100"
	Cone 3	2.652" – 3.822"
	Cone 4	3.432" – 5.148"
Wheel width setting range		1.5" to 20"
Wheel diameter setting range		1" to 35"
Wheel diameter measurable with sensor		10" to 28"
Shaft weight capacity		165lbs (75Kg)
Voltage required		115V 60 Hz Single Phase

Installation Dimensions

