



ADG Tire Changer Performance Specifications



| MODEL >> | Raptor | M-944 | G-122 | M-914 | M-912 | G-112 |
|---------------------------|-------------------------|----------------|----------------|----------------|----------------|----------------|
| Design style | Center hold – leverless | Pneumatic Tilt | Pneumatic Tilt | Swing Arm | Swing Arm | Swing Arm |
| Inside clamping capacity | unlimited | 13" to 26" | | 13" to 26" | 13" to 23" | 12" to 24" |
| Outside clamping capacity | unlimited | 10" to 24" | | 10" to 24" | 10" to 20" | 10" to 20" |
| Turntable rotation speed | Var 6-15 rpm | Var 6-15 rpm | | 8 rpm | 6.5 rpm | 6 rpm |
| Max tire diameter | 42" | 40.56" | | 47" | 41" | 44.5" |
| Max tire width | 15" | 14" | | 14" | 12" | 14" |
| Wheel width range | | 3.5" to 13" | | 3.5" to 13" | 3.5" to 11" | 3.5" to 13" |
| Required air supply | 145 psi | 145 psi | | 145 psi | 145 psi | 145 psi |
| Electrical requirements | 230V Single Ph | 230V Single Ph | | 115V Single Ph | 115V Single Ph | 115V Single Ph |
| Shipping weight | 836 lbs | 602 lbs | | 619 lbs | 472 lbs | 506 lbs |

Designs and Performance Specifications are subject to change without notice