

Nationwide Network of Professional Equipment Distributors

1-800-497-0009 • www.ADGequipment.com



Your Local Automotive Service Equipment Professionals

Sales - Installation - Service

## AUTOMOTIVE AND TRUCK EQUIPMENT

### Sales, Installation & Service for all your Equipment Needs

WELCOME to your best Local Source for Sales, Installation, Service and On-Site consultation for Automotive and Truck Service Equipment.

We are your local merchant, here to support you and your business's needs now and into the future. We are not a Web seller featuring lowest cost Chinese products. From Tool Carts to 100,000 lb Truck Lifts and everything in between we offer you competitive prices coupled with on-going service support for all your equipment needs.

Looking for a particular brand or model? Not a problem. As a member of the Industries largest network of Independent Automotive Service Equipment Distributors we have access to a huge variety of industry leading brands. One call is all it takes.

### TABLE OF CONTENTS

Duplicate numbered pages with F after number are Forward lift pages.

PRODUCT PAGE	S	PRODUCT	PAGES
AIR COMPRESSORS18,19,	21	LIFTS - TRUCK	30F,31F,35,36,37
AIR CONDITIONING60,61,62,63,64,6	65	LIFTS - SCISSORS	33
AIR DRYERS		LIFT - UTILITY	32
AIR PIPING SYSTEMS24,	12	LIFT - INSPECTIONS	39,40
BALANCERS9,10,11,12,13,	17	LIFT-MAINTENANCE & PARTS	38,39
BALANCER ACCESSORIES15,	16	LIFT - WHEELS	50
BENCHES52,53,	54	LEAK DETECTORS	51,60,61
DIAGNOSTICS	51	LUBRICATION	.41,42,43,46,47,66
EXHAUST SYSTEMS22,	23	PRESSES	59
FINANCING	67	REELS	42
JACKS - FLOOR57,	58	SHOP EQUIPMENT	50,56,57,58
LIFTS - 2POST25,25F,26,26F,27,27F,	35	SHELVING	54
LIFTS - 4 POST28,28F,29,29F30F,31	F,	STRUT COMPRESSORS	50
34,34F36,36F37,37F	55	TANKS	48,49
LIFTS - INGROUND30,	31	TIRE CHANGERS	3,4,5,6,7,8,9
LIFTS - MOTORCYCLE	33	WASTE OIL HANDLING	44,45





























## HIGH PERFORMANCE TIRE CHANGER



Ultra
High Performance
Lever-Less
Tire Changer



Scan for product video

The traditional Mount/Demount head has been completely redesigned eliminating the need for the 'tire pry bar'. This amazing design eliminates the need for excessive physical effort by the technician.



### **Leverless Head Feature**














Coordinated top and bottom rollers offer multi-function versatility for Clamping Tire, Positioning Tire & Rim assembly and loosening beads. All functions are controlled from an ergonomically located control panel.

## CENTER HOLD DOWN TIRE CHANGER

# Model M-940

# Lower Cost Ultra HP Tire Changer





Scan for product video


- · Leverless Pneumatic mount/demount head
- Bead press arm depresses top bead and holds it in the drop center during remount preventing premature bead seating.
- Center hole securing of wheel eliminating clamps
- 180 degree single arm bead breaker (Patent Pending) for precise, reliable and rapid bead breaking on both sides of tire







Pneumatic lateral arm movement allows for placement of bead breaker on bottom side of tire













# LEVERLESS TIRE CHANGER

# M-944HP-LL

Our Strongest Most Durable Work-horse Tire Changer

Designed for High Volume Shops





Scan for product video

# Features Include:

- Lev erless Mt/De mount head design (see pics below)
- Equipped standard with multi-function side mounted Pneumatic assist tool.
- Variable speed turntable 6 to 15 rpm
- 'Inside clamping 26", outside clamping 24" expandable to 28" with optional adapters'
- Massive steel cabinet and superstructure
- 633 lbs of durable steel construction for years of dependable high volume service.

Pneumatically operated leverless head automatically secures the tire bead and raises it above the rim edge (demount cycle) eliminating the need for the Tire Pry bar







# HIGH PERFORMANCE TIRE CHANGER

# M-924HP3

## A Great Combination of Cost & Value



- Standard full function Pneumatic Assist tool with Centering cone, Top roller, bottom lift disc, bead press arm
- · Side mounted bead breaker with standard polymer edge protection



Inside clamping 26", outside clamping 24" expandable to 28" with optional adapters





Foot pedal activated Pneumatic tower tilt









## SWING ARM TIRE CHANGER



- Expanded range swing arm handles 15" rim width and 45" OD tires
- Side mounted bead breaker with scratch resistant blade cover
- Inside clamping 26", outside clamping 24" expandable to 28" with optional adapters
- Water Separator and Oiler standard
- Surge tank in the column saves floor space for compact installs





# VALUE SWING ARM TIRE CHANGER

# G-112HP1

Item# 8A Model

Ítem # 8B Model

## For Passenger Cars and Lt Trucks

Ideal for Light to Medium Volume Shops



Inside clamping 26", outside clamping 24" expandable to 28" with optional adapters

### Model G-112HP3

with left side mounted pneumatic bead assist







# SAVE HUNDREDS ON COMBO PURCHASE

**Ask about Trade-In opportunities** 







## **ECONOMY WHEEL BALANCERS**

# G-240 Durable Entry Level Computer Spin Balancer





- Industrial 40mm shaft handles Tire/Wheel combinations to 150 lbs
- Captured back spring simplifies the mounting process
- · Attached data entry arm for measuring distance out, manual entry
- Multi-tiered weight storage tray includes area for tape weights





- · Simple touch panel data entry system with easy to follow icons
- Standard wheel guard protects the technician





Durable Mid Range Computer Spin Balancer

- Two parameter auto entry, Distance and diameter at touch of the wheel
- Foot pedal operated shaft lock, prevents accidental wheel roll when applying weights
- · Large easily readable display board
- · 40mm Industrial shaft with quick nut



Raised digitlal display with wheel graphic, Large weight storage.

Two parameter auto entry standard on G-250-2D, Third parameter entry arm added for Model G250-3D

Foot pedal activated shaft lock prevents accidental tire roll during weight placement



## SPACE SAVING BALANCER

# M-3200

# M-3200 Two Parameter Auto Entry Balancer Ideal for space challenged shops



 Industrial 40mm Diameter shaft with standard Speed nut and captured back spring for the ultimate in speed and versatility.



 Standard safety hood accommodates tires up to 44" diameter



 Optional tape weight holding clip available for parameter entry arm, assists in accurate tape weight placement



 Model M-3200 offers the ability for the technician to program in whether they prefer to apply weights at 3:00, 6:00 or 12:00 on the wheel. Balancer automatically recalculates amount dependent on what is easier for the technician.



 Optional wheel lift easily raises Tire/Wheel combinations up to 150 lbs to the balancer shaft height, eliminating the risk of technician back strain.

## LASER BALANCER

# M-3350

All the features you need for today's wheels...simply and ergonomically combined



Weight Placement

- ✓ Advance laser weight placement ...Standard
  - ✓ Two parameter auto entry ...Standard
  - ✓ Third parameter auto entry ...Optional



LASER WEIGHT SPOTTING WHITE LED ILLUMINATION



TWO PARAMETER DATA ENTRY



OPTIONAL THIRD
PARAMETER
AUTO ENTRY

## LASER BALANCER

# M-3650

# Laser Weight Spotting PLUS Motor to Weight Position and Hold





External sensor for wheel width data entry (optional)

- Bright white cabinet mounted LED's illuminate the inside of the wheel for easy and accurate weight placement
- Cabinet mounted high intensity laser pin-points exactly where to place the weight. No More Guessing, No More Do Overs



13B M-3650-3D Shown

13A

Side accessory cabinet offers easy storage for cones. colletts and flange plates, keeping your work area organized





Automatic data entry of diameter and distance out with one touch of the wheel. Advanced software allows placement of weights at 3, 6 or 12 o'clock, operator programable.

Large durable weight tray features pockets for 30 different weight styles/weights plus mounting cone storage



### **MONDOLFO FERRO**

# Why we feature Mondolfo Ferro Wheel Service Products



- With Manufacturing based in Mondolfo Italy, Mondolfo Ferro is a World Leader in Wheel Service Equipment
- With over 50 years of Wheel Service Equipment experience, Mondolfo Ferro offers state-of-the-art Engineered products with field proven designs.
- Owned by the Nexion Group Company, Mondolfo Ferro enjoys collaboration with eight sister companies including Corghi-USA and SICE.
- Shared Engineering & Manufacturing resources around the world allow Mondolfo Ferro to be at the leading edge of all Wheel Service designs
- With five decades of World Class design & Manufacturing, Mondolfo has built a Worldwide reputation for durability & dependability in their complete line of Wheel Service products
- Quality, Innovation, Service! For 52 years customers around the globe have trusted Mondolfo







### Why ADG (the Automotive Distributions Group, Inc.)?

As a member of the largest Automotive Service Equipment Distributor trade group, we have access to hundreds of products and back-up service parts.

Fielding a nationwide organization of Professional Equipment Distributors, ADG has partnered with Mondolfo Ferro in order to insure our customers have access to a wide array of Tire Changers and Wheel Balancers to handle all of today's Tire/Wheel combinations

We are here to handle all your shop needs.....

Global Product Access - Nationwide Distribution - Local Representation

# LUG CENTERING



# **Lug Centering**

Balancing begins with centering and centering is either reinforced through lugs or the actual centering point for truly lug centric wheels (aftermarket wheels) where the wheel is centered by the lugs rather than the hub. With either Quick Plates or Flange Plates, the lug mount on the vehicle is replicated exactly on the balancer and provides the same resistance to side to side movement pushing the wheel away from the centered mount.

# Supreme Centering Solutions

## New North American Flange Plate Kit



New North American Flange Plate Kit 200 259 409 SUPERCEDES 200 249 409

- Provides Even
   Pressure From
   Front Mimics
   Luq Nuts
- No Contact With Wheel Surface
- Dynamic ImbalanceSolution
- Wall Chart Included

**H**ange Plate "A" **P**art#241e702 409

**A**ange Plate "B" **P**art# 251e802 409

**F**lange Plate "C" **P**art# 251e903 409

**P**ange Plate "D" **P**art# 261e702 409

Stud II (Includes 8) Part# 271 804 118

**Stud III (Includes 5)** Part# **271** 904 119

**Stud V (Includes 8)** Part# **271** 994 121

Storage Trolley Part# 900 008 128

### **BALANCER ADAPTERS**

**NEW SoftGrip Quick Nuts** 







- New ergonomic design with soft-touch handle
- Upgraded threaded jaws with bigger bearing surface allows a higher torque and prevents opening under load

Lower overall height - allows the use of Flange Plate and QuickPlate even on short threaded shafts

SoftGrip		Old Style
Α	34.5mm	40mm
В	7.5mm	21mm


Longer life of the threaded jaws - thanks to new metal alloy  Optimized glide prevents fast wear of the threaded shaft

## **Latest Solutions to Today's Mounting Problems**

### **World Innovation**

The Revolution in Wheel Balancing VARIABLE FLANGE PLATES

- Fully adjustable for bolt patte 95 182 mm
- 🎒 For all 4, 5 and 6lug rims on passenger cars & SU
- No time-consuming search for the suitable bolt pattern
- Exchangeable spring loaded bolt-heads for different rim types
- Locking of the correct bolt pattern via the new ProLoc-System
- Unbeatable results and repeatability in conjunction with the "DuoExpert"
- HAWEKA Quality Made in Germany



QuickPlate



В

Problems safely mounting Clad Wheels without damage ??

We have the perfect solution!



Haweka pin plates and collets can solve your problems.!

No clad surface contact, perfect Balancing!

Do It Right the First Time



# DIAGNOSTIC LASER BALANCER

# M-4000C

The **Ultimate** Computerized Balancers

> tem# 17 Model





The user-friendly graphic interface, together with the latest touchscreen technology on 22" widescreen monitor simplify and speed-up all operations and program selection.



Weight tray ergonomic and functional. It features many large trays to house all different types of counterweights and various tools.

Rear cabinet mounted laser accurately measures Tire

and Wheel during measuring runout. Provides runout of tire and rim solving difficult Wheel Assembly diagnostics

White LED's light up the

inside of the wheel for



Scan for product video

Wheel and tire runout is laser measured and graphically displayed in Tire Matching procedure





Pneumatic Clamping with foot pedal operation





Red Laser spots the tape



## RECIPROCATING AIR COMPRESSORS

# CHAMPION® Advantage Series

The Industries Most Trusted Name in Compressed Air

### **Factory Installed Options include:**

### **1** Magnetic motor starter

For thermal overload protection.

#### 2 Air-cooled aftercooler

The factory mounted, heavy duty, air-cooled aftercooler effectively reduces up to 65% of the moisture from discharged compressed air. (Optional on 5HP, standard on 7HP and larger)

#### 3 Automatic tank drain

Automatically discharges excess moisture from the receiver.

### 4 Vibration isolator pads

Isolates the compressor unit from the foundation or floor. Reduces noise and protects the unit from any out-of-level floor situation that could cause vibration and damage.

#### **5** Low oil level monitor

Low Oil Level Monitor shuts down the unit when oil levels are below an adequate level. Prevents the unit from restarting if oil levels are not at an adequate level.



- Ships within24 Hours
- ▶ 5 Year Warranty on Tank, Pump & Motors

Simplex - 1 Motor, 1 Pump						
MODEL	VR5-8	VR7F-8	VR10-12			
HP	5	7.5	10			
TANK	80	80	120			
CFM	17.3	23.1	34.8			
ITEM#	18 <b>A</b>	18B	18C			

Duplex - 2 Motors, 2 Pumps						
MODEL HR5D-12 HR7D-12 HR10D-						
HP	5	7.5	10			
TANK	120	120	250			
CFM	17.3	46.2	69.6			
ITEM#	18D	18E	18F			

# ROTARY VANE AIR COMP

# CHAMPION® LV-Series

The Industries Most Trusted Name in Compressed Air

# Quiet as a Rotary Screw... Dependable as a **Piston Compressor**

### **FEATURES INCLUDE:**

- Available with Single or Twin Compressors
- Continuous Run or Start/Stop
- Standard 2 year warranty
- Industry leading 10 year warranty available



So Quiet, It Doesn't Need It's Own Room!

Item # 19B

Model

Vertical

## COMPRESSED AIR DRYERS

# Refrigerated Compressed Air Dryers INSURANCE FOR ALL YOUR SHOP EQUIPMENT

# YOUR SHOP RUNS ON AIR Pneumatic hand tools • Lifts Pneumatic shop tools • Spray booths • Tire Changers

- Keep it running smoothly with Clean, Dry, Refrigerated air
- Quality HG and HGE Series dryers improve productivity, reduce maintenance expenses, ensure optimal performance
- Rugged Powder Coated sheet metal cabinets coupled with sealed R-134A refrigeratnt systems endure years of harsh shop environment



Model	Item #	Rated Flow rate (scfm)	Height (in)	Width (in)	Depth (in)
HG15	20A	15	15	13	13
HG25	20B	25	22	15	15
HG35	20C	35	22	15	15
HG50	20D	50	22	20	20
HGE75	20E	75	20	19	21
HGE100	20F	100	21	13	30
HGE125	20G	125	21	13	30
HGE150	20H	150	21	13	30

# RECIPROCATING AIR COMPRESSORS

# GHAMPION® Evolution

### 5 - 15 HP QUIET ENCLOSED RECIPROCATING AIR COMPRESSORS

- Clean, professional appearance
- Highly effective sound deadening enclosure



Looking for the advantages of Reciprocating Compressor and the Low Noise level of a Rotary Screw? Time for you to consider Champion's Worldclass Evolution models

#### 5 hn

קוו כ										
<b>I</b> tem Number	Lubrication	Unit Config.	Tank Config.	Tank Size (Gal.)	Model Number	Pump Model	ACFM 175 PSIG	RPM	Approx. Ship Wt. (Lbs.)	Item Number
21A	Colock	Cimamlay	Base	N/A	BER5	RP-15B	16.8	734	505	19A
21B	— Splash —	— Simplex —	Horiz	80	HER5-8	RP-15B	16.8	734	733	19B
7.5 hp										
21C	— Splash —	Simplex —	Base	N/A	BER7F	RP-15B	22.4	990	534	19C
21D	— Spiasii —	Simplex	Horiz	80	HER7F-8	RP-15B	22.4	990	762	19D
10hp										
21E	— Splash —	Simplex —	Base	N/A	BER10	RP-30D	34.1	740	950	19E
21F	— Spiasii —	Simplex	Horiz	120	HER10-12	RP-30D	34.1	740	1220	19F
15hp										
21G	— Splash —	Simplex —	Base	N/A	BER15F	RP-30D	46.6	1045	1040	19G
21H	SpidSII —	simplex	Horiz	120	HER15F-12	RP-30D	46.6	1045	1310	19H

\*Units tested in accordance with CAGI/PNEUROP Acceptance Test Code PN2CPTC2.

# RAIL SYSTEM EXHAUST EXTRACTION

# APEXRAIL SYSTEM easily provides EXHAUST REMOVAL to ALL your Bays









## Unique patented Vacuum Holster hose retraction system




- High Strength extruded aluminum Rail System
- Looks great and provides an infinite number of Trolley locations to remove exhaust

Vacuum Holster design requires dampers be closed for Hose Retraction

- Saves Heated and Cooled air from being pulled out of shop
- Insures hoses don't end up laying on the floor
- All components 100% MADE IN THE USA





- Overhead Rail system supplies Exhaust Removal to multiple bays.
- Vacuum assist hose retraction makes storage fast and easy
- Systems custom designed for your shop



Scan for product video

## FIXED DROP EXHAUST EXTRACTION



### AIR SYSTEMS




# HIGH PERFORMANCE COMPRESSED AIR PIPING SYSTEM

### BENEFITS OF ProAIR FOR YOUR SHOP AIR REQUIREMENTS:

- Clean Professional Appearance
- No Corrosion Aluminum Extruded Piping
- Systems Can Be Easily Disconnected, Modified or Expanded Later
- Optional Water Trap Tees Reduce Moisture Throughout the System

- More Efficient Air Delivery
- Reduced Pressure Loss
- Higher Flow Rates
- Tested to ANSI Standards






CALLUS TODAY TONE
CALLUS TODAY
AND HATE
ESTIMATE

### CUSTOM SYSTEMS AS SIMPLE OR AS COMPLEX AS YOUR PLANS!

Expanding...
Improving...
Upgrading
Your Shop...
We've Got
Your Air
Supply
System...



## CHALLENGER 2 POST LIFTS

### Model SA-10 10,000 lb Symmetric or Asymmetric

May be installed in symmetric or asymmetric configuration, dependent on your shop work load

- Adjustable Height and width options
- 3-stage front arms, 2-stage rear arms
  - Double telescoping screw pads
    - Single point mechanical lock release
      - Wide rubber door impact guards

Item # 25A

### Model E-10 10,000 lb Symmetric or Asymmetric

• Exclusive **Versymmetric® Technology** provides a versatile **2 Lifts in One™** Design to safely lift vehicles symmetrically or asymmetrically within the same service bay

- 2' column height extensions available
- 3-stage front arms
   2-stage rear arms
- Double telescoping screw pads
- Single point mechanical lock release

Item # 25B



CL Challenger Lifts



#### **CL10V3 Features & Benefits:**

- Standard offset arm design provides **directSPOT**<sup>™</sup> to vehicle's front lifting points for built-in productivity
- Double telescoping screw pads adjust from 4-7/8" to 6-3/8" reducing the need for adapters
- Rubber door guards protect vehicles from door damage when accessing driver controls
- 11'8" standard height allows lift to be placed in standard service bay with 12' ceiling
- Single-point mechanical lock release system allows technician to disengage both column locks simultaneously
- 48" elongated carriage design decreases load on bearing

# 110 10,000lb 2 POST LIFT



**Specifications I10** 10,000 lbs. (4536kg) Capacity Rise 77" (1956mm) Overall Height 143-1/8" (3635mm) Height to Shut-Off 136-1/4" (3461mm) Minimum Ceiling Height 144" (3658mm) Minimum Lifting Height 3-5/8" (93mm) 131" (3327mm) Overall Floor Width or optional 137" (3479mm) 109-3/4" (2787mm) Inside Column Width or optional 115-3/4" (2940mm) 97" (2463mm) Drive Through or optional 103" (2616mm) 1-1/2" (38mm), Adapter Heights 3" (76mm), and 6" (152mm) 208/230v, 20 amps Voltage/Amps

2 HP/1Ø\*

Motor/Phase

Spot-Rite<sup>TM</sup> 3-Stage Front


to accommodate vehicles

both asymmetrically

and symmetrically.

Arms - Allows the I10

# DP-10 10,000Ib DIRECT PULL LIFT



# MEDIUM DUTY 2 POST LIFTS

# **CL12 Medium Duty Symetric Lift**





#### standard features:











\*Part#: 10318

# **E12 Medium Duty Symetric Lift**



**C**Challenger Lifts

26B

#### Features & Benefits:

- Heavy-Duty 2-stage telescoping arms provide excellent reach. and retraction to accommodate vehicle lifting points
- 13' 10" or 14' 7" adjustable column height accommodates. higher profile vehicles and provides maximum headroom to work undemeath vehicles
- Optional 2' column height extensions accommodate higher profile vehicles
- Heavy-Duty telescoping Screw Pads adjust to multiple heights minimizing the need for adapters
- Padded overhead shut off system prevents vehicle damage. from being raised too high
- Single-point mechanical lock release system allows technician to disengage both column locks simultaneously
- Rubber door guards protect vehicle from door damage.
- Premium powder coat finish provides long-lasting durability
- Plated Arm Restraints and Arm Pins inhibit rust and provide long-lasting durability

Optional 2' Column Height Extension Available



# 112 MEDIUM DUTY 2 POST LIFT



#### **I12 Series Features:**

- 12,000 lbs. capacity for raising most passenger cars, trucks and vans.
- The I12 is third party certified by ALI.
- Hydraulic cylinders in each column
  - Full stroke
  - Cylinder rod concealed inside carriage
- Overhead cable equalization.
- Single point lock release
- Large rubber-padded swivel adapters with extra height extensions (4-1/2" and 8-1/2") are standard.
- Spring operated arm restraints, disengage at floor level.
- Padded overhead height limit switch bar.
- Durable powder coat finish standard color of lift is blue with yellow arms. Red lift with yellow arms also available at no extra cost.
- · Adapter storage bracket kit

#### **Available Options:**

- Special truck adapters
- Air/Electric work station with air regulator and oiler



# HEAVY DUTY TRUCK LIFT



# 15,000 or 18,000lb **Heavy Duty Truck Lift**

#### Features & Benefits:

#### · NEW

3-stage front and 3-stage rear arms gives extended reach and retraction making it easier to lift a wider variety of cargo carrying vans.

#### Lower profile

Standard pad adapter is 16% lower than the standard 15,000 lb capacity 2-post lift to accommodate lower profile cargo vans.

#### Ease of operation

Single point air actuated lock release allows technician to disengage locks in both columns simultaneously.

- Stronger and more durable designed Oversized steel pulley reduces stress on equalization system and provides increased durability.
- Greater load spread 60" lifting carriage helps to provide a more equal spread of weight which can prevent premature column wear.

#### Safety engineered

Padded overhead shut off system prevents vehicle damage should a vehicle come in contact with he overhead shutoff bar.

Model#: 15000-35

tem


27A

15,0001

Heavy-Duty Cargo Vehicle 2-Post Lift

15,000 lb. capacity





dard Adoptes are not competable with 18 model #16000 (16,000 to coposity) 2-post lift with 2-stage area

Lift comes with 5" and 10" truck adapter

extensions

# DP015 HEAVY DUTY TRUCK LIFT



Engineered to Perform...

Built to Last!

Padded shut-off bar to prevent damage caused by lifting a vehicle too high





Powder coat finish; more durable than conventional finishes

DP015	DP015-2	
15,0	00 1bs.	
88-1/2"		
5-3/8"		
14'7"	16' 7"	
13' 10"	15' 10"	
14' 8"	16' 8"	
12'4"		
117"		
109"		
5-3/8" - 7-3/8"		
10-3/8"		
15	-3/8"	
208/230v, 20 amps		
2 H	P/1Ø*	
	15,0 88 5- 14'7" 13'10" 14'8" 12 1 5-3/8" 10	

\*Optional 3-phase available. Specifications subject to change without notice or liability



High tech gear style arm-restraints allowing quick and easy placement of the lift arms

# **GENERAL SERVICE 4 POST LIFT**


# **CL** Challenger Lifts

15,000 lb Four Post - General Service or Alignment



# 4015series

4-Post Flat Deck General Service & Alignment Rack Package Lifts



### Features & Benefits:

- The highest rise in the industry provides more work space underneath vehicles
- Single point air actuated lock release disengages all column locks simultaneously
- 14 level locking positions for a variety of alignment and general service tasks
- Compatible with the industry's latest camera imaging alignment systems
- Recessed stainless steel turning radius gauges provide accurate readings

- 80" rear recessed free floating slip plates offer a wider range of 4 wheel alignment capabilities
- Durable non-skid louvered approach ramps for positive vehicle traction and technician safety
- Fully gusseted base plate and top shroud reduces column deflection and is less sensitive to uneven floors
- Large 9-1/2" heavy-duty steel pulleys with Teflon® bearings, plated steel pins and 1/2" cable diameter reduces wear on cable suspension system

## CR14 GENERAL SERVICE RUNWAY LIFT



- 14,000 lbs. Capacity
- NEW taller column design adds a 78-3/4" rise height providing techs better vehicle service access
- NEW improved heavy duty high-performance cable and sheaves system
- Durable powder coat finish
- Easy to use single point lift operation with clear access to one button air operated lock release

Item # F28A Model CR14

## **CRA14 ALIGNMENT RUNWAY LIFT**

- 14,000 lbs. capacity
- 18 level/lock positions
- Rear wheel slip plates standard
- Internal airline standard
- FLR (filter, lubricator, regulator)
- Two (2) 7,000 lbs. Capacity Rolling Jacks
- Carbon Steel Front Radius Plates



### CRO14 OPEN FRONT LIFT



- NEW patent pending articulating shaft design ensures even roller loading for longer life
- Multi-position lock components allow lift to be level at any lock position
- Optional rolling bridge jacks with a capacity of up to 7,000 lbs.
- NEW 41" louvered ramps for improved drive on traction, wheel chocks automatically engage when lift is raised
- polymer rollers protect floors and provide quieter operation
- NEW Taller roller spacing reduces the load on rollers for longer life
- NEW taller open front column design adds a 78-3/4" rise height providing techs better vehicle service access
- Runway can handle wheelbases up to 215"

# MEDIUM & HEAVY DUTY 4 POST LIFTS



18,000 lb


Medium Duty 4-post
General Service or Alignment lift

- High tensile strength leaf chain with sealed roller bearings for smooth reliable hoisting
- Multi-point internal lock ladder
- Single point lock release
- Diamond plate anti-skid runways
- Adjustable width between runways 36"-54" handles cars, vans, pick-ups, med duty work trucks

**CL** Challenger Lifts



# HEAVY DUTY 4 POST



# 18,000LB GENERAL SERVICE



#### **Additional Features:**

- Self chocking approach ramps in the rear
- Single point latch release system
- · Multi-position lock components
- Non-skid surface on runways
- · All hydraulics and mechanical lifting components concealed under runway

#### **Available Options:**

- Rolling bridge jacks (RJ9, 9,000 lbs. capacity each)
- Drive Through ramps optional
- 30 gallon oil drain pan



Designed for Performance....Built to Last!

# **CHALLENGER INGROUND LIFTS**

# EnviroLift® Electric Hydraulic Inground Lifts

 All In-ground mechanisms enclosed in polymer housing cassette

- Large 8.5" Chrome pistons
- Use less shop space and present a cleaner less cluttered shop appearance
- Wide range of lifting accessory and add-on options
- Available in 10,000, 12,000 or 15,000 lb capacities
- 50% more bearing contact than competitors
- · 3 stage front and rear arms







### How do we achieve accelerated lifting?

We have increased the motor and pump size which provides a faster rise and descent. These components increase the rise of speed from 48 seconds to 27 seconds equating to a 42% time savings.

Lowering speed is held to a constant 17 seconds (approximately) regardless of the weight of the vehicle.





Increasing revenue potential just got

faster!

up in 27 sec.

down in 7 sec.

regardless of vehicle weight

# **CR30 HEAVY DUTY FOUR POST**



- Diamond plate surface on runways and ramps
- · Single point latch release system releases all four column locks at the same time
- Multi-position lock components allow lift to be level at any lock position
- · Self chocking approach ramps engage in the rear when the lift is raised
- · All hydraulics and mechanical lifting components are concealed under the runway
- Internal airline connections allow two rolling bridge jacks to operate at the same time
- Capable of handling vehicles up to 30,000 lbs. with wheelbases up to 307"



Specifications	CR30/CR30-3		
Capacity	30,000 lbs.	Runway Height	8-3/8"
Maximum Wheelbase	271"/307"	Runway Width	24"
Lifting Height	68"	Width Between Runways	41" - 48"
Overall Length	28'-8-1/8" <b>/</b> 31'-8-1/8"	Rise Time	105 seconds
Overall Width Overall Height	12'-4-13/16" 7'-3/4"	Voltage Single Phase (optional 3-Phase available)	208/230
Width Inside Columns	132"	Motor	4 HP
Length between Columns	285"/321"	Minimum Bay Size	16' X 33'

Specifications subject to change without notice or liability

## CHALLENGER ENVIRO LIFT



## Lifting Point Configurations

3-stage frant and 3-stage rear swing arms with double telescoping screw and removable rubber pads

Model#: AV1020WV 10,000 lb. capacity\*

Drive-on fixed pad with 4-way directional adjustable sliders

Comes standard with (4) 4-1/8" multi-position rubber spotting blocks

Model#: AV1020AP 9,000 lb. capacity"



AV1020 series





## HD TRUCK DRIVE-ON FOUR POST

## CR50 / CR60

HEAVY-DUTY FOUR POST DRIVE-ON LIFT

Robust design and user-friendly features provide the value you need in a heavy-duty drive-on lift.

50,000 AND 60,000 POUNDS Item # F31A odel CR50 50,000lb CAPACITY



1 0 p 0

E - E - E

E STOP Button

4 E 

ि छ 🎍

#### **Optional Accessory**

#### LED LIGHTING

High-efficiency LED lighting, single touch operation system provides hands-free lighting under the vehicle from the lift' control panel.



Shown: M140002

#### PATENTED CONTROL SYSTEM - Operate lift from

ANY post with this exclusive control system

- Position memory lifting cycles are configured and set - turn each column on, lock the columns and go
- Programmable controls show operational status for each column plus, program a height limiter - maintains level within 3"
- Real time height reading
- Battery Indicator
- · E-Stop button located at each panel
- · Audible descent alarm.

Item # F31B Model CR60 60,000lb



Accommodates wheelbases up to 33'



Shown: CREOMUCCO (60,000 lbs. capacity)

#### LOW DRIVE-ON HEIGHT

Ramps and runways accomodate a variety of vehicle types. Optional drive thru ramo kit avallable.

#### ANCHORED COLUMN SUPPORT

Four easy to install wedge style anchors secure each heavy duty column to the floor

## PORTABLE & SHORT RISE LIFTS

# **CL** Challenger Lifts



Challenger Lifts' Portable Mid-Rise Lift is a great way to increase the productivity in a shop. It's like having a service bay anywhere, indoors or out.

The motor is conveniently mounted to a Heavy-Duty tow dolly, making it easy to move and operate on almost any solid surface.

Exclusive features include a sliding/rotating arm design with rubber pads, low drive-over clearance, and much more.



**Model#: MR6**Portable Mid-Rise Lift 6,000 lb. capacity

Item # 32A

MR6



Item # 32B

SRM10



Model#: SRM10 10,000 lb. capacity Short-Rise Lift

**Th**e SRM10 is a great choice for brake and tire servicing needs. Dual hydraulic cylinders provide a 10,000 lb. lifting capacity picking up vehicles ranging from small passenger cars to light trucks.

Standard 2 position spotting blocks and auxiliary adapters reach a wide range of vehicle pick up points. Lug nuts and other small parts are always within reach with the SRM10's inset storage trays. Its small footprint compared to other lift models make the SRM10 a perfect fit.

## 6,000 LB MID-RISE LIFT



## FRAME OR PAD CONTACT LOW RISE TIRE SERVICE LIFT

F32B

**F32C** 

0.00018





**Features** 

- 10,000 lbs. capacity or 7,000 lbs. capacity
- Drive-over ramps and side rails provide the width to support wider vehicles during approach
- Dual lifting cylinders provide the power required to lift a 10,000 lbs. vehicle
- The TL10 comes with four 3-position adapters, four 3" rubber blocks and four 1-1/2" rubber blocks for added height.








The TL07 comes with four 3" rubber blocks and four 1-1/2" rubber blocks.



## SCISSORS LIFT

## 7,700 LB OPEN CENTER SCISSORS LIFT





Manufacture provided 60" (standard length) air and hydraulic hoses allow three ergonomic, recommended power console placement options.

- Can be surface mounted or recess flush mounted
- Synchronized hydraulic system eliminates the need for center obstruction bar
- Diamond plated flip-up approach ramps allows the platform to accomodate longer wheel base vehicles
- Includes eight rubber spotting blocks; four 3" and four 1,5"
- 74.5" rise height



## MOTORCYCLE LIFTS



Shown:1000MCL 1,000lbs.capacity (Side Extensions not shown)

#### Models 1000MCL & 1000MCLDT (Drop Tail)

- Front wheel vise prevents wheel movement during securing, lifting and maintenance.
- Foot pedal controlled air valve operates on 100psi air.
- Rearsection (for the Droptailversion) is removable for complete rear wheel access.
- Side extensions are standard for ATV and additional vehicle service. The motorcycle lift comes with a wheel vise and two 12" extensions, making it great for motorcycles, ATVs, lawnmowers, golfcarts, etc.

Specifications	1000MCL 1000MCLDT
Capacity	1,000 lbs.
Rise	33"
Min. Height	7-1/4"
Length with Ramp	113"
Length without Ramp	93"
Width of Platform	24"
Width with ATV Adapters	48"
Air Requirements	90-100 PSI
Shipping Weight	690 lbs.



Shown: BJ10 Included with purchase of 1000MCLDT

Specifications subject to change without notice or liability



Shown: 1000MCL 1,000lbs. capacity (with Side Extensions)



## WHATEVER VEHICLE YOU NEED TO LIFT....WE'VE GOT YOU COVERED!



## 4-POST HOBBYIST/PARKING LIFT



**Multiple Power Unit Locations** 


The power unit can be placed either on the front column of the drivers side or the back column of the passenger side of the lift. This provides convenient power control accessibility and versatility for any garage layout.

Model#: CL4P9X
Home/Commercial
Storage 4-Post Lift
9,000 lb. lifting capacity
Storage Application



#### **Storage Application**

It's the best of both worlds. Service your vehicles or store them up top. With 80" rise height, most full size vehicles are easily parked underneath for everyday use. Optional drip tray set completes the storage application, keeping any fluids from contacting the vehicle underneath.



#### Service Application

Professional grade quality with 80" high rise and multiple lock positions is perfect for light duty service up to 9,000 lb. capacity. Optional rolling jacks and jack trays provide quick tire and brake work access.

## OST HOBBYIST/PARKING LIFT



- ALI/ETL Certified
- Multi-position locks allow runways to be level at any lock position
- Single point lock release
- Includes steel approach ramps
- Perfect for home use
- Powder coat finish
- Includes jack tray
- Includes wheel caster kit



Exclusive adjustable lock ladder leveling system

Specifications	EFP9
Capacity	9,000 lbs.
Rise	85"
Overall Length With Approach Ramps	218-1/2"
Overall Length Without Approach Ramps	197"
Approach Ramps	31"
Overall Width With Motor	133"
Overall Width Without Motor	121"
Runway Tread Width	19-1/2"
Runway Length	188"
Runway Height	5"
Width Between Runway Treads	39-1/4"
Outside Runway to Outside Runway	78-1/2"
Clearance Under Runways	80"
Clearance Between Columns	109-1/2"
Drive Through Width	97-1/2"
Height of Columns	97"
Power Unit	110 Volt (220 Volt Optional)

Specifications subject to change without notice or liability.

## HEAVY DUTY 2 POST LIFTS

## **A Complete Line of Heavy Duty Two Post Lifts**

Features Engineered To Meet The Most Demanding Truck Facilities



7/8" Forklift Mast Steel Column Construction

4 Inch Sealed Steel Carrier Bearings

Separated 44" to Better

Distribute Bearing Load



Three Piece Telescoping Lift Arms



Automatic Gear & Sprocket Arm Restraints



Mechanical Lock Ladders in each Column



Single Point Lock Release (Air or Electronic Control Depending on Model)

## Č

### Clear Floor.....Clear Top • Hydraulic or PLC (E-Model) Equalization

Model	PK-16	PK-16E	PK-18	PK-18E	PK-20	PK-20E	PK-22E	PK-26E*	PK-30E*
Capacity (lbs)	16,000	16,000	18,000	18,000	20,000	20,000	22,000	26,000	30,000
Equalization	Hydraulic	PLC Control	Hydraulic	PLC Control	Hydraulic	PLC Control	PLC Control	PLC Control	PLC Control
ETL Certified	YES	YES	YES	YES	YES	YES	YES	NO	NO
Item Number	35A	35B	35C	35D	35E	35F	35G	35H	35I

\*Installation requires in-floor mounted subframe

## MOBILE TRUCK LIFTS

## **MOBILE COLUMN LIFTS**



12,000 TO 180,000 LB CAPACITIES

## Lift virtually any vehicle, anywhere, for inspection or service



- Available in 12, 18, 20, 24, 30, or 40,000 lb lifting capacity per column
- Available in sets of 2,4,6 or 8 columns (total capacities to 320,000 lbs)

#### **Hardware Features**

- ◆ PLC Control with proximity sensors and electric selonoid locks
- ◆ Two structural designs avaiable (see model chart on Pg 4):
  - Quad design of 4 2" x 4" steel HSS Tubing supports using UHMC glide blocks
  - 7/8" ForkLift mast steel columns with 4" sealed steel bearings
- ◆ Rubber coated steel wheels with pallet style jacking
- ♦ No mechanical screws or bearings to wear out

◆ Premium PPG Alkyd Enamel Finish with Titanium Dioxide

◆ 1/4" chain driven proximity sensors accurately control column height



#### Features & Operational Benefits

- Two equilization methods available (see model chart on Pg 4):
  - Programmable Logic Control (PLC) with one Master column controlling all others
  - Printed Circuit Board Control using "pair mode" operation allowing pairs to be separated
- ◆ Electric Hydraulic full rise lifting (67" to bottom of fork) in 66 seconds
- ♦ Single point electric solenoid lock releases, dead man style operation
- Nineteen locking positions (one every 3") for safe versatility in work heights
- ◆ Adjustable forks handle wheels from 22" to 48" diameter, standard 12" fork length (optional 22")





#### Mobile Column Lifts Available - 24,000 to 180,000 lb Capacities

Model	12-2PC	12E-2PC	12-4PC	12E-4PC	12-6PC	18-2PC	18W-2PC	18E-2PC	18-4PC	18SB-4PC	18W-4PC	18E-4PC	18WE-4PC	18SBE-4PC
Total Set Capacity	24,000	20,000	48,000	44,000	72,000	36,000	36,000	32,000	72,000	72,000	72,000	68,000	64,000	64,000
Number of Columns	2	2	4	2	6	2	2	2		4	4	4	4	4
UHMC sliding blocks										Х				
4" steel roller bearings	Х	Χ	Χ	Χ	Χ	Χ	Χ	Χ	Χ		Χ	Χ	Χ	Χ
ETL Certified									Χ			Χ		
Ext legs for dual tires		Х		χ			Χ	χ			Χ	χ	Χ	Χ
Model	18WSB-4PC	18WESB-4PC	18-6PC	18SB-6PC	18E-6PC	20-2PC	20-4PC	20-6PC	24-4PC	24-6PC	30-4PC	30-6PC	4-4PC	
Model Total Set Capacity	18WSB-4PC 72,000	18WESB-4PC 64,000	<b>18-6PC</b> 108,000	<b>18SB-6PC</b> 108,000	<b>18E-6PC</b> 64,000	<b>20-2PC</b> 40,000	<b>20-4PC</b> 80,000	<b>20-6PC</b> 120,000	<b>24-4PC</b> 96,000	<b>24-6PC</b> 144,000	<b>30-4PC</b> 120,000	<b>30-6PC</b> 180,000		
Total Set Capacity			108,000	108,000	64,000	40,000		120,000		144,000		180,000	160,000	
Total Set Capacity Number of Columns	72,000 4	64,000 4	108,000	108,000 6	64,000	40,000		120,000	96,000 4	144,000 6	120,000	180,000	160,000 4	
Total Set Capacity Number of Columns UHMC sliding blocks	72,000 4	64,000 4	108,000	108,000 6	64,000 6	40,000	80,000 4	120,000 6	96,000 4	144,000 6	120,000	180,000	160,000 4	

## HEAVY DUTY 4 POST LIFTS

## **Custom Manufactured 4-Post Truck Lifts**

Lift Capacities and Runway lengths to fit your needs

(20,000 - 125,000lb capacities)



#### **Manufacturing Features:**

- Four Lifting hydraulic cylinders, one per column, provide Powerful Direct Drive Lifting
- ◆ Equilization by either Hydraulic (18-40,000 lb capacites) or PLC Control (50-120,000 lb capacities)
- ♦ No Cables, No Chains, No Overhead Obstructions
- ◆ Each hoist is equipped with either two 2 HP Pumps (12-50,000 lb capacities) or four 2 HP Pumps (50-125,000 lb capacities)
- ♦ In column ladder locks for safety
- ♦ Air Solenoid Actuated Single Point Lock Release
- Structurally reinforced runways fabricated by Box Type welding eliminates deflection under load

## **Optional Models Available:**

- ◆ Standard runway lengths from 17' to 40'. Custom lengths available
- ◆ Runway widths of 24" or 30" diamond steel surface





#### Four Post Models Available - 12,000 to 125,000 lb Capacities

Capacity	20,000	30,000	35,000	40,000	50,000	60,000	70,000	80,000	100,000	125,000
Pumps (2 HP)	2	2	2 4	2014	2 4	4	4	4		
Lengths Available	20'	21'-33'	21'-33'	21'-33'	25' - 40'	30'-40'	30'-45'	30'-45'	35'-40'	35'-40'
Runway widths	24"	24"	24"	24"	30"	30"	30"	30"	30"	30"
Equilization	PLC	PLC	PLC	PLC	PLC	PLC	PLC	PLC	PLC	PLC
Item Number	37A	37B	37C	37D	37E	37F	37G	37H	37I	37J
ETL Certified		Χ	Х	Χ						

<sup>\*</sup> PLC models feature Lifting cylinders in each column

<sup>\*</sup> Custom lengths available

<sup>\*</sup> Drive-Through Ramps available

## POWER UNITS

# Replacement Power Units for 2-post and 4-post lifts



#### **Motor**

208-230V AC 3450 RPM1PH 60 Hz

#### **Pump**

AFC 2.0 CC/Rev. (0.122 Cu. In./Rev.)

#### Relief

Fixed at 2750 PSI (191 Bar)

#### **Nominal Endhead**

9/16-18 SAE Pressure-Return Port 3/8 NPTF Aux, Return Port Plugged)

#### **Tank**

4.0 U.S. Gallon Vertical Tank Down Mounting 700 Cu. In. Useable

#### Valving

Manual Release Valve (Cartridge-Style) Check Valve (Cartridge-Style)

#### Wiring

230V AC to Motor Momentary "On" Switch



## PORTABLE POWER UNITS

## **COMPACT, LIGHTWEIGHT AND PORTABLE.**

SINGLE-SPEED PUMPS DESIGNED TO DRIVE SINGLE- ACTING CYLINDERS.

- The power unit of choice for major manufacturers of auto body, frame straighteners and other equipment.
- Operate at 40-100 psi shop air pressure at the pump.
- dBA 85 at 10,000 psi.
- Serviceable pump motor is not a "throw away", providing economical repair.
- Permanently vented reservoir cap.
- Internal relief valve protects circuit components, air inlet filter protects motor.



## LIFT SERVICE & INSPECTIONS

## LIFT SERVICE

We carry Service and Accessory Parts for virtually every lift.

From Rubber pads to replacement Power Pack units,

cables and cylinders.



One call handles all your lift needs 1-800-497-0009

## LIFT INSPECTIONS

Protect your Employees from Work Place Accidents caused by Lift Failures Reduce your risk of Litigation by voluntary compliance with OSHA standards



The Automotive Lift Institute (ALI) recommends that Automotive and Truck lifts undergo annual inspections. We offer comprehensive inspections and Preventative Maintenance Programs to insure on-going safe operation of your automotive and truck hoists. Services include:

- On-site Lift Inspections & Reports
- On-site Lift Maintenance
- · Lift Accessories & Service Parts

Call today 1-800-497-0009 to schedule your shop inspection,

and rest easier tonight!

## LIFT MAINTENANCE

## PROTECT YOUR EMPLOYEES...PROTECT YOUR BUSINESS

Poorly maintained lifts can subject your employees to unnecessary work area risks. Cables can wear, cylinders can lose seals, safety locks can hang-up. When you're lifting a 20,000 lb vehicle you have a lot more to lose then some billable hours.





## PREVENTATIVE MAINTENANCE PLANS AVAILABLE





Make sure your valued employees are operating well maintained equipment.

## FLUID INVENTORY CONTROL

# 

#### BOM

- 1 3110-018 Printer Interface Module
- 1 3110-019 PC Interface Module
- 1 3110-020 Tank Control Module
- 1 3120-068 LED Display
- 2 3110-016 Standard Keypads
- 2 3110-017 Multi-Point Dispense Module (MPDM)
- 6 Pulse Meter/Solenoid Valve Kits select the meter to match the fluid type
- 3 3120-033 Air Solenoids
- 1 3120-069 Ticket Printer
- 3 Tank Level Sensors select the sensor for fluid & method

#### **Synergy Fluid Monitoring Systems**


Today, the needs of our customers are more complex, the fluids are many, and the challenges of managing and accurately monitoring these fluids are difficult. Wireless has its limitations, communication problems, and risks with all electronic controls mounted in the handle. Synergy brings you real—time information with seamless communication without interruption.

control fluid dispenses in a workshop from a single central

· The Director Jr. will also manage a solenoid valve to

control the air powering the pump.

## **Systems that Monitor every Ounce for you!**



Sales, Service or Installation call 800-497-0009

· Fluid measurement in pints, quarts, gallons, or liters

· Service fluids: motor oils, synthetics, ATF, gear oil,

record-keeping

and anti-freeze

location

## HOSE REELS

## **Signature Series Reels**

Specifically configured bracket for easy installation

Eight position locking precision die cast latch mechanism, with secure easy-touch pull release

Machined thick wall hub parts for high strength and pressure capability

**Heavy gauge stamped** rims, outlet arm, base, and spring case

Easy hose replacement due to single-arm outlet design

Five-position outlet arm for ceiling, wall, or tank-top hose reel mounting

Tangential outlet position to reduce hose bending over outlet rollers

Wide six-roller outlet prevents hose pinch, reduces hose wear

Ball stops are included with hose



Item # 42A 50' Oil

Item # 42B 50' Air

#### Easy to install

Compact design to fit small spaces Ceiling, wall, tank mount, cabinet or mobile lube

#### Proven design


Excess spring torque assures a reliable hose return Power spring is designed for high reliability

#### **Built to last**

Thick wall fluid swivel and hub Heavy gauge stamped rims, arms, and base Wide-beam structural design for stiffness

#### Full range of model choices

30-, 40-, and 50- ft hose lengths available Styles for air, water, oil, and grease Custom powder coat paint colors available



## **Evolution Hose Reel: an Evolution in Design and Performance**

This hose reel is an Evolution in design and performance. Lightweight but extremely rugged: steel pedestal and arm, and dual ball-bearings. The Evolution is a solid performer. The Evolution combines design, performance, and reliability with the right features and benefits for today's customers. All Evolution series reels have a narrow and lightweight design; includes hose, hose stop, and a 2.5' connecting hose.



- Superior Structural Design and Stability
- Fully Ported Shaft and Pressure Balanced Swivel
- Easy Installation Mounting and Accessories
- Fluid Compatibility for Multiple Applications
- Eight-Position Latching Mechanism
- Easy On-Site Tension Adjustment
- Spool Mounted on Dual Ball-Bearings
- Superb Corrosion Resistance
- Multi-Positioning Outlet Arm
- High Quality Long Life Power Spring
- Easy Maintenance and Service
- 2.5' Inlet Connecting Hose Included



## PUMPS & CONTROL HANDLES



## **PISTON PUMPS | PANTHER® HP 3:1**

#### Features:

- Pressure relief on Panther Series models bolt-on safety feature reduces premature wear of hoses and seals.
- Mechanical air valve more reliable, no stalling and no icing.
- Designed for lower air consumption extends compressor life.
- Built in muffler results in quiet operation and eliminates icing.
- Stainless steel pump rod reduces corrosion and extends seal life.
- Double acting pump delivers consistent fluid flow with greater dispensing accuracy.








## **Trusted name in Lubrication products** for more then a Century





The DR meter carries with it new innovative technology in a digital meter. Our new meter is precision balanced, lightweight and ergonomically designed. Simple, accurate and efficient, this meter combines new features with proven oval gear technology.



- Meter housing: unique totally encased polycarbonate housing provides superb impact resistance while isolating the electronic register module (ERC) from the environment providing an airtight seal with the meter body.
- Sealed battery compartment: battery clips are mounted directly on the ERC, no cables for battery contact, which ensures protection against the environment, impact, or vibrations.
- Low power consumption: ERC with auto-sleep function for improved battery life.
- Trip mode function: resettable totalizer function can operate as an economical, simple fluid inventory control system.
- Non-resettable totalizer function: shows total fluid flow through the meter and is unaffected by low or dead batteries.
- All new handle: aluminum body with lightweight ergonomic soft grip handle for comfort and precision balance.
- Unique ¼ turn manual tip: effective and very fast, high flow, no splash and very easy to use.
- Flange coupling at the control valve: eliminates the use of connection adapters which can become loose, providing superior integration of the meter and handle.
- Swivel cover: protects automobiles from nicks and scratches.
- Large ported swivel: for comfort even at high pressures, includes durable inlet filter which protects meter from debris.
- Trigger lock button: prevents accidental dispense and also allows the gun to be locked in the open position.
- · Affordable repairability: ERC can be changed easily.
- Various wands available: including new 'Memory Flex" wand which is shown. Available in ¼ turn & automatic tips



Item

#43C

DR Meter

## WASTE OIL HANDLING



## FLUID EVACUATORS

#### **FEATURES**

- · Capacity:17gallons
- Extractusedoilandotherfluidsfromanyvehicle-safer,cleaner
- · No more stripped drain plugs
- · Greatforcars, boats, motorcycles, and smallengines
- · Easilyremoveoverfills
- · Vacuum-chargedunitiscompletelyportableandeasytouse
- Includessixsuctionprobes(metalandflexible)
- · Suction probes equipped with quick-disconnect couplers
- · AdaptersforBMWandVolkswagenincluded
- Self-evacuatingfeaturemakesemptyingcleanandeasy
- · Clearbowlcapacity:2gallons
- · Service bulletin SB4045



Oil Evacuator with Clear Dome and Merced Aslapter

## **OIL DRAINS**

#### **Balcrank Roughneck II**

#### **Features**

- 19.25" diameter catch basin features an inlet filter screen and s-hooks for tools.
- Fully adjustable bowl height from 47 to 74 inches.
  - "Splashguard" bowl design prevents splattering, speeds drainage.
  - · Seven foot evacuation tube provides sight gauge for fluid level.
  - Tank handle makes maneuvering easy.
  - Patented automatic fluid evacuation valve eliminates gravity draining, pouring, or the need for an evacuation pump
  - 23 gallon storage tank; fewer drain intervals
  - A low pressure safety valve prevents over pressurization of tank
  - Clear evacuation hose; provides fast fluid evacuation and shows fluid levels in tank
  - Heavy gauge, all-steel construction guarantees long life.
  - Tip-resistant balanced design
  - Large diameter rear rubber wheels and non-marking wide front casters maneuver the toughest shop floors.



#### **Balcrank Spillguard**

#### Features

- · Capacity: 16 gallons
- 41" to 65" telescoping bowl height
- 19.25" bowl with screen
- Male drybreak coupler included for top port evacuation
- · Drum dolly included
- Level gauge
- Antifreeze drains painted with green powder coat



## WASTE OIL DRAINS



## 18 Gallon Model 8874


- Comes with 16.5" funnel
- Extends from 40" to 73"
- Metal trolley comes with 4 casters and pull handle for safe and easier movement around the shop
- Oil can be drained either by pour or gravity,
- Integrated drain valve or using integrated bung hole with rotary barrel pump (not included)

Item # 45B




## **Cantilever Waste Oil Drain**

& Evacuator Model 8888



- Maximum unit height of 60.25", Minimum unit height of 35.25"
- Basin height of 10.25", 74" reach

Item # 45C



#### Low Profile Waste Oil Drain w/Pump Model 8878 | 18 Gallon

- Ideal for oil draining trucks where a pit or hoist is not available
- Large 18 Gallon baffled tank captures oil and transports with ease
- Convenient rotary hand pump facilitates easy evacuation to large oil tanks
- Large metal screen
   Long steel handle eases moving and positioning of drain

  | Item#45D

## OIL BARS & SPIGOTS

## **OIL BARS**

## **OIL BAR STATIONS**



#### Custom to your requirements

#### **OIL BARS**

4200-014 - Oil Bar



#### Features:

- Up to four dispense points Heavy duty, Metal body
- Drain with steel screen and 1/2" NPT hose connection
- Oil bar ships with one spigot. For two-, three-, and four-spigot oil bars, order additional spigots 4200-012.
- Max. pressure 1,000 PSI (68.9 bar)
- · Welded materials Steel, Aluminum
- Spigot inlet 3/8" NPTF

#### **SPIGOTS**

**Dispenser Spigots**: Featuring smooth trigger action, anti-splash flow diffuser and shutoff valve.750psi. Available in gooseneck style for transfer pumps and straight stem style (1"M,3/8"F)for oilbars.

00-00 Gooseneck 3/4" NPT(M)00-005 Straight Stem for Oil Bars

00-00SpigotOnly

**00-00** Gooseneck 1/2" NPT(M)



#### **TANK ACCESSORIES**


**Tank Level Gauges:**Mount on tank bung fitting. Display dial shows the remaining fluid depth in inches as the attached float level changes. For stationary tanks only. Not recommended for mobile lubers.

50-00	60"
50-00	36"
50-005	32"
50-009	72"



#### **PUMP SENTINEL**

Pump Sentinel allows for the controlled dispensing of fluids. The unit is capable of preventing fluid theft by utilizing rocker switches to enable or disable up to six pumps via a master key which is needed to turn on the system. The console also prevents fluid spills during non-working hours by using a built in timer which will turn off the air supply to all pumps at a predetermined time each day.



## Features

- Capable of preventing fluid theft by using switches to enable or disable up to six pumps
- · Master key needed to turn system on
- 6' cable to run to junction box

46

• Small Console footprint: 6.5" L x 5" W x 3" H




## OIL SYSTEMS

## Custom designed systems to meet all your fluid needs

Tank Storage Steel lines Reels Handles

- Size, Location, Poly or Steel, Single Wall or Double Wall
- Stainless, T's, Ball Valves
- 50', 75' 100'
- Metered, Mechanical, Digital















**Call for On-Site Consultation and Quotation** 

## POLY STORAGE TANKS

## 



♦ Stackable Poly Tanks

◆ Translucent for fast sight inventory recap

Clean & efficient shop appearance

Capacities : 45, 80, 120, 180, 225, 310

## STEEL STORAGE TANKS







# Steel Storage Tanks

Single and Double wall units available

Varying Thickness'

#### Multiple Shapes including:

- Ob Round Horizontal- Rectangular
- Ob round Vertical- Dike tanks
- Bench Storage- Skid Tanks

#### Various sizes

- ♦ 275 Gallon- 500 Gallon
- ♦ 330 Gallon- 1,000 Gallon

#### **Available Finishes**

• Primer Red - Industrial Enamel





## PNEUMATIC STRUT COMPRESSOR



A Plastic Tray











D Front Protection Guard
Scan for
product video

F Twin Foot Pedals

**E Bottom Helper Plate** 

## LM-200 PORTABLE WHEEL LIFT



- Lifts up to 160 lb. tire/wheel assemblies
- Rises to full height in approx. 10 seconds
- Steel tire rollers for easy lug nut alignment
- Offset design allows easy access to lug nuts
- Easily transport tire assembly to balancer or changer
- Swivel casters make it easy to maneuver
- Foot lever brake ensures you are locked in place
- Made in the USA

#### **Features**

#### Safety and Protection

The two parking brakes ensure the lift will not move when in use. The cable and rollers are enclosed to protect it from dirt and other debris.

#### Low Center of Gravity

The mobile tire lift stabilizes the load utilizing the four rollers and a low center of gravity.

#### **Rotating Casters**

All caster wheels rotate a full 360° for greater maneuverability and easier movement around the vehicle.

#### **Air Operated Control**

No batteries to charge, always ready to operate. Safe neutral center, Raise, Lower toggle valve for easy up/ down positioning.

#### Storage and Convenience

The mobile tire lift has a tool and lug nut storage area located on the lift.



Scan for product video

## DIAGNOSTIC LEAK DETECTION



The OEM Approved Smoke Pro® Total-Tech® is the world's best-selling diagnostic leak detector, and guaranteed to be the most profitable tool you will ever own. Smoke Pro® gives technicians full-featured diagnostic capabilities to detect, locate, and repair leaks in sealed systems. This compact, yet powerful machine not only finds more repair jobs, it helps you sell those repairs to your customers.

#### Find More Repair Jobs

Find leaks and sell the repair to your customer with visual confirmation.

#### Greatly Reduce Diagnostic Time

One simple connection diagnoses an entire system in seconds so that technicians can repair more vehicles in less time.

#### Improve Accuracy of Repairs

Eliminate comebacks by verifying that leaks are repaired completely.

#### Pays for Itself in Less Than 30 Days

With this tool, garage owners expedite diagnostics, improve accuracy in repairs, heighten customer satisfaction, and increase profits, making Smoke Pro® the most valuable tool in any repair shop.



## SMOKE MACHINE



- New safer, healthier technology. Uses no heat to create high visibility smoke
- Using 0.5psi pressure control, Cool Smoke has the highest flow rate of any smoke machine
- Instant, high performance vapor enriched with UV dye
- · Ready for future EVAP Systems
- Rugged housing and built-in adapter storage
- Uses 12 volt DC with only 1 amp draw rate

Excellent return on investment. One service per day will pay for the machine in a few months!

## WORKBENCHES

## WORK BENCHES & SHOP FURNITURE by



" Create the work space of your dreams"

## **Wall Mount & Portable Benches**











Basic wall mount

Basic w/backstop & sliding doors

Tool storage cabinet & overhead shelf

w/ sliding doors Custom wood tops or Stainless Steel Tops

## **Tear/down - Fluid Containment**









Flat Top

w/ back stop

Extended

Deluxe Fluid Containment

## **Specialty Shop Furniture**



**Advisor Station** 



Service Cabinet



Tech Carts



Cabinet with overhead storage & lighting

## DELUXE WORK PLACE SYSTEMS

## WORK BENCHES & SHOP FURNITURE by

" Create the work space of your dreams"





You spend 40+ hours a week at your work station

We can help you make it comfortable and versatile!





**Lift Control Options** 





**Integrated Reel Options** 



## SHOP FURNITURE

## **Tool Carts & Custom Bench needs** by

" Create the work space of your dreams"















Lift Concealment Cabinets
Portable Tool Carts
Carts lockers
Recycle Cabinets
Reel cabinets
Service Writer
Technology Centers

## STORAGE & HANDLING



General Shelving • Bulk Shelving
High-Density Heavy-Duty Drawers
Essential Tool & General Storage
Pre-Configured Product Specific Shelving
Parts Department Support Equipment
Tire Handling • Bulk Tire Storage • Service Counters



## REAR SLIP ADD-ON KIT

## Easy To Service And Repair

- (2) 59 1/2" x 20" Full Floating Rear Slip Plates
  - Plastic base prevents rusting.
    - · Simple Installation on most general service lifts
      - Available in four different rear ramp configurations

#### **Features**

Lets you position the turn plates in the location best suited to individual vehicle positioning

Turn Plates Not Included but are available in black powder coated mild steel or stainless steel

See below diagram for length options available.


Custom Sizes Available

# Stainless Steel Option Available



Scan for product video

#### DB-6000 Rear Slip Plate Add-on Kit Configuration Guide.



## SHOP EQUIPMENT

#### 4000 LB. CAPACITY FOLDABLE ENGINE CRANE

AFF Model 3582 Engine Hoist is engineered for speedy and efficient removal, mounting and transport of automobile and light truck engines. Ideal for auto shops with limited floor space and perfect for maximum portability. Also good for rental yards.





#### **4000 LB. CAPACITY ENGINE CRANE**

MODEL 3580b

A high capacity engine crane with added boom length, enabling it to be used on vehicles with long front ends where an extra long reach is required.

- Boom extends between 49" and 76"
- Base legs extend between 60" and 80" to maximize stability
- Frame legs increase from 26" to 33" in width at full extension
- Roller-bearing swivel casters with safety brakes to secure positioning

Shown with optional Model 582 Engine Tilter

#### 10-TON CAPACITY TRUCK JACK STAND

MODEL 3309A

- - Pin-type post adjusts to seven height positions from 18-1/2" to 30"
  - Large 3-1/8" x 5-7/8" support saddle and wide 17" x 17" base
  - · Convenient carrying handle
  - Sold individually
  - Ship weight 37 lbs.

Item # 56C

#### 6-TON CAPACITY JACK STAND SET

**MODEL 3306** 

Item #

56B

• 6 ton capacity, adjusts from 15-1/2" to 23-3/4" and has a 9" x 10-1/2" base

· Ship weight 30 lbs. per pair

Item # 56D



#### AFF 3320A UNDER-HOIST STAND 1650 LB. CAPACITY

AFF 3320A Under-Hoist Stand adjusts from 54-1/2" to 80-1/2" and has a footoperated lever for extra lift.

Item # 56E

#### AFF 3233A STABILIZING STAND 2 TON

Stabilizing Stand adjusts from 66-1/2" to 73" and has a bearing included for smooth operation. The stand also has an adjusting screw for easier load positioning.

Item # 56F



#### **LOW-PROFILE 1200 LB. CAPACITY TRANSMISSION JACK**

· Designed for light truck transmissions

MODEL 3171

 Fully adjustable universal saddle with corner brackets and safety chains

 Safety overload bypass to prevent hydraulic damage

• 24" handle pivots 360° around pump

Item # 56G



## FLOOR JACKS

#### 3-1/2 TON PROFESSIONAL HEAVY-DUTY DOUBLE-PUMPER FLOOR JACK

MODEL 350SS

- Lifts from 4" to 19-1/2"
- Pinned steel saddle (1-1/8" stud) with rubber pad for added vehicle protection
- Rear-mounted 2-3/4" swivel casters for ease of maneuverability
- · One-piece 50-1/4" padded handle parks upright



MODEL 300T

- Low pick up point of 3.75" (1/4" lower than 350SS)
- High height of 21.5" (2.0" higher than 350SS, 1.5" higher than 200T)
- Universal joint technology for precise release valve control
- Tough powder-coated frame for longer shop life
- Pinned steel saddle (1 1/8" stud) with rubber pad for added vehicle protection
- Safety valve to prevent overloading
- Plungers use a 'U' Cup design instead of O ring, for a better seal
- Centered pump plunger design offer 20% longer life over offset
- Release valve porting is designed for slower controlled descent
- Pump design engages sooner for longer stroke

Item #

57A



Item #

#### 10-TON CAPACITY HEAVY-DUTY **LONG-CHASSIS JACK**

**MODEL 3130** 

- · Long 61" body for easier lifting of vehicles with long overhangs
- · Extra-wide stance for additional stability



#### 5-TON CAPACITY HEAVY-DUTY AIR/HYDRAULIC **LONG-CHASSIS JACK**

MODEL 3125

• Operates at 115-200 PSI, 7.8 cubic feet per minute

· Long 56" body for easier lifting of vehicles with long overhangs



#### 22-TON AIR/HYD AXLE JACK W/ 3PC EXT KIT

Model 565E

- Heat treated cylinder wall and chromed piston give added stability and longer jack life.
- · Alloy steel lifting mechanism for added durability and operator safety
- · Precision engineered tolerances for maximum performance
- Lifts between 8-3/4" to 23"
- In-line filter to protect air motor from contaminants
- Corrosion-resistant aluminum and nylon composite air motor
- Ram extension kit included with 3/4", 2-3/4" and 4" extensions
- · Large 7-3/4" rear wheels for easy positioning
- Automatic in-line oiler to lubricate air motor



MODEL 544

Super duty construction make this unit virtually indestructible and is what is required for effortless and trouble-free lifting of dump trucks or garbage trucks up to 44 Tons. Second to none, this jack gets the job done.

- 41" "T" handle and large rubber tires for easy, smooth movement
- · Heat-treated cylinder wall to protect against scoring
- Precision engineered tolerances for maximum performance

Item # 57F



Item#

57E

## END LIFT JACKS



#### 5-1/2 TON LONG-REACH AIR END LIFT (Left Picture) **MODEL 3596**

Designed for heavy-duty low-profile vehicles that require a longer reach in order to be securely lifted at the vehicle front axle or frame and can also be used on the bumper. The scissor action design and full shop air operation (200 PSI) provide more lift height under low-profile vehicles. Using its multiple saddle sizes and adjustments along with its standard drop-axle adapter it can lift from as low as 6-1/2" to a high 53-1/2" with a long 48" forward reach.

- Steel saddles adjust between 23" and 45" widths to accommodate a wide variety of vehicle applications
- 48" Forward reach (distance from cylinder to saddles)
- Two saddle sizes and drop axle adapter increase versatility
- · Three-way heavy-duty air valve for precision lifting
- · Automatic safety lock engages in five preset positions . Two large pneumatic wheels for easy maneuverability

#### 10-TON AIR END LIFT (Right Picture)

#### **MODEL 3598**

The AFF Air End Lift is designed with an extra-wide stance to lift the entire front or rear of large trucks, buses, industrial, heavy-duty construction equipment, and large farm vehicles.

- 10-ton capacity achieved at 200-PSI air supply
  4" x 6" steel saddles adjust between 36" and 50" widths to accommodate a wide variety of vehicle applications
- Saddle arms reversible for low height loads
- Three-way air valve for fine lifting and lowering control
- Automatic mechanical safety lock engages at five lift heights from 17-1/2" to 50"
- Two air control valve fittings one for shop air supply and one for a Schrader valve
- · Front swivel caster and two pneumatic rear tires for easy maneuverability
- . 13" Forward reach (distance from cylinder to saddles)





## TRANSMISSION JACKS

Item # 58C

#### TRANSMISSION JACK 1100LB CAPACITY

MODEL 3190B






- · Fully adjustable universal saddle with spring-loaded corner bracketsfor easy "tool-free" adjustment
- Use this jack to remove and install fuel tanks by ordering AFF Fuel Tank Adapter #3198 (sold separately)
- 2009 ASME/PALD compliant

#### 2200 LB, CAPACITY TELESCOPIC TRANSMISSION JACK

MODEL 2195B

Two-stage telescopic ram, designed for heavier automotive and medium-duty truck transmissions, transfer cases or differentials in under-hoist applications.



· Automatic safety valve provides critical overload protection

· Adjustable saddle with corner brackets and safety chain





## BENCH AND FLOOR PRESSES



#### **SHOP PRESS 12 TON**

MODEL 812

- Designed for light duty applications
- Seven level bed adjustments
- Unit has 6 3/4" stroke
- 3" bed rail opening with 16" post opening
- 70" tall with 20" base width





#### 20-TON CAPACITY FLOOR PRESS

MODEL 820A

- · Automotive and light industrial use
- · Eight level bed adjustment
- 20-ton bottle jack with overload protection
- Heavy-duty return springs for fast ram retraction
- · Reinforced head plate





#### **30-TON CAPACITY FLOOR PRESS**

MODEL 832A

- Automotive and light industrial use
- · Eight level bed adjustment
- 20-ton bottle jack with overload protection
- Heavy-duty return springs for fast ram retraction
- Reinforced head plate

Item # 59C Model 832A



#### **50-TON CAPACITY FLOOR PRESS**

MODEL 837

- Heavy-duty vehicle and industrial use
- Winch-operated press bed with seven adjustment levels
- Two-speed hand pump provides faster travel to load while air/hydraulic pump (with overload protection) provides effortless

operation

• Frame-mounted hydraulic pressure gauge



## A/C DIAGNOSTICS

## CHOOSING THE LEAK DETECTION KIT THAT'S RIGHT FOR YOU:



## YOUR CHOICE OF INJECTION SYSTEMS.

The original Spotguh is versatile and economical

Storage case

The Spotgun Jr. is perfect for controlling inventory through the use of single application cartridges

## YOUR CHOICE OF CHEMISTRY DEPENDING ON YOUR NEEDS.

- super concentrated UV Dye, plus friction modifiers, anti wear additives and antioxidants.
- Also available with Universal A/C Dye

#### **YOUR CHOICE OF UV DETECTION LIGHT.**

Not all UV lights are created equal!

- 12V Mega-Lite<sup>™</sup> and Micro-Lite<sup>™</sup> provide strong, reliable power any time
- UV Phazer BLACK offers extreme performance and outstanding versatility
- LED-Lite offers an economical UV light



Part No. Injection System	Application	UV Light	Onty/Size	UPC	Unit (inches & lbs)				
Fairt Nu.	rart No. I injection system	мринсации	OV LIGHT	ŲIILY/∂I£G	uru	Length	Width	Height	Weight
414500A		A/C ExtenDye	Micro-Lite	8 oz / 240 mL	628604004585	17.00	13	5	6.55
414565A	Cnotaun	A/C ExtenDye	UV Phazer BLACK (Rechargeable)	8 oz / 240 mL	628604004608	17.00	13	5	6.10
414565	Spotgun	Universal A/C Dye	UV Phazer BLACK (Rechargeable)	8 oz / 240 mL	628604004066	17.00	13	5	6.10
415400		Universal A/O Dye	Mega-Lite	8 oz / 240 mL	628604001492	17.00	13	5	6.80
332005A			UV Phazer Black (AAA Battery)	4 x 1 oz / 30mL	628604004561	14.00	11	4	3.6
332010A		A/C ExtenDye	Pico-Lite	1 oz / 30mL	628604005247	14.00	11	4	3.6
332220A	Spotgun Jr.		Pico-Lite	2 x 1 oz / 30mL	628604005261	14.00	11	4	3.6
332005		Universal A/C Dve	UV Phazer Black (AAA Battery)	4 x 1 oz / 30mL	628604004042	14.00	11	4	3.6
332220		Universal A/G Dye	Pico-Lite	2 x 1 oz / 30mL	628604002642	14.00	11	4	3.6

	Replacement Parts and Accessories for Leak Detection Kits								
471111	Spotgun Injection Gun Kit: (3) injection guns, (3) R-134a Hoses and (1) Hanger Bracket	471540	1234yf Spotgun Hose Assembly with coupler						
4/1111	(1) Hanger Bracket	471546	Spotgun Jr. R-134a Hose / Coupler						
98007111	Spotgun Hanger Bracket	471547	1234yf Spotgun Hose assembly with coupler						
471112	UV Enhancing Glasses	981470	R-12 Aluminum adapter						
471535	R-134a Hose / Coupler: Twister & Spotgun injector systems	982564	Service Stickers: strip of 32 service stickers						
471536	High Side adapter: R-134a	98000010	Spotgun Jr. Injection Gun						
471539	Spotgun Injection Gun	98011025	Spotgun Jr. Hose - High side						

## A/C DIAGNOSTICS

## **CHOOSING THE INJECTION KIT THAT'S RIGHT FOR YOU:**



#### INJECTION KITS

Everything you need to service A/C systems -fast!



#### YOUR CHOICE OF INJECTION SYSTEMS.

- The original Spotguil is versatile and economical
- The Spotgun Jris perfect for controlling inventory through the use of single application cartridges
- The ECO-Twist" system is the perfect entry-level injection tool




#### YOUR CHOICE OF CHEMISTRY DEPENDING ON YOUR NEEDS.

- A/C ExtenDye is formulated with super concentrated UV Dye, plus friction modifiers, anti wear additives and antioxidants.
- Also available with Universal A/C Dye
- A/C Oil is a perfect companion to SAE A/C recovery units
- LeakGuad™ is formulated to safely and permanently stop small leaks

#### A/C EXTENDYE<sup>™</sup>

Several years of engineering went into creating this all new dye. A/C ExtenDye™ has four unique features:

- 1. Super-concentrated UV dye detects leaks quickly, saving time and money. A/C ExtenDye is proven to fluoresce brighter than the competition. And there's no need to use more. Use the same quantity of A/C ExtenDye per application as our Universal A/C dye.
- 2. Friction modifier increases lubricity (less friction) of the compressor oil, improving efficiency (friction coefficient) by over 50% and improving fuel economy.



- 4. Antioxidant stops the oxidation process, reduces acidity and prolongs oil life.
  - SAE J2297 certified for use in
  - R-134a and R-1234yf systems
  - Hybrid safe
  - Solvent-free



When combined, we refer to this exciting new additive package as QuietCool" Technology.



#### a/c extendye'" CARTRIDGE

Works exclusively with the Spotgun Jr.™ injection system

399020A 399020AEU 1 oz Winged 399006A

0.25 oz 399006AEU 0.25 oz Winged



#### A/C EXTENDYE" CARTRIDGE

Works exclusively with the Spotgun™ injection system

499108A



#### BOTTLE 399020A1 oz Bottle 399006A0.25 oz Bottle



#### A/C EXTENDYE™ BOTTLE

Exclusive new bottle design with accurate dosing chamber 499008A

## A/C RECHARGE & RECOVERY

34788NI Premier R-134A Refrigerant

Recovery, Recycling, Recharging Unit

Robinair 34788NI machines recover, recycle, evacuate, leak-test and recharge R-134a with improved 98.5% efficiency – unmatched by any competitor. The new design features a larger graphical display, automatic features including leak testing, automatic refrigerant refill and oil drain/inject – putting A/C lubricant back into the system.

#### Other features and functions:

- Fully-Automatic Function
- Automatic Oil Drain
- Oil Inject
- Refrigerant & Oil Database
- Save & print before and after service data
- Visual & Audible Alarm
- Vacuum Leak Test
- Automatic Air Purge
- Automatic Refrigerant Refill
- Vacuum Feature
- Multilingual Display
- Refrigerant Management System
- Optional Printer
- Optional Refrigerant Identifier

Item # 62A Model 34788NI





34788NI-H Hybrid Premier R-134A Refrigerant

Recovery, Recycling, Recharging Unit

Robinair 34788NI-H machines recover, recycle, evacuate, leak-test and recharge R-134a with improved 98.5% efficiency – unmatched by any competitor. The new design features a larger graphical display, automatic features including leak testing, automatic refrigerant refill and oil drain/inject – putting A/C lubricant back into the system.

#### Other features and functions:

- Fully-Automatic Function
- Automatic Oil Drain
- Refrigerant & Oil Database
- Save & print before and after service data
- Visual & Audible Alarm
- Vacuum Leak Test
- Automatic Air Purge
- Automatic Refrigerant Refill
- Vacuum Feature
- Multilingual Display
- Refrigerant Management Systc...

ROBINAIR

AN SPX BRAND

62B

Works with Hybrid & Non Hybrid Vehicles



## A/C RECHARGE & RECOVERY

# One button for fully automatic recover/recycle/evacuation/recharge



#### 37880 Series features include:

High-side or low-side charging.

- Fully automatic air purging constantly monitors and purges non-condensables.
- Fast tank refills with no hose changes.
- Refrigerant management system that keeps track of information on A/C service work.
- Twin 1/2 hp compressors for speed and reliability.
- Automatic shut-off for full tank and high pressure.
- Heavy duty shock resistant scale for accurate charging.
- Two-stage, 3/5 cfm vacuum pump for fast, high-efficiency evacuation.
- Fully factory tested after a 34-point quality check.
- Built-in self diagnostics.
- Maintenance reminders for oil and filter changes.

## RMS 37887 with unique flush feature for use with high voltage compressor A/C systems.....

- Allows simple and quick clearing of the service hoses to minimize PAG oil contamination.
- Reduces oil contamination well below allowable amount.
- Eliminates the need to worry about cross contamination of oil.
- Fully automatic.
- 50 lb. storage tank.
- Also available with integrated printer and identifier (37888).
- Extended
- OEM approved for use on high voltage A/C systems (37887 and 37888).

For a complete line of A/C service tools and accessories, visit your local distributor or www.yellowjacket.com.

## NEW 1234YJ REFRIGERANT RECYCLERS

## **Newest Model 1234-6 AC Service**

#### **FEATURES**

- Fully automatic operation program for service, walk away and return when complete.
- ✓ 95% recovery efficiency
- Programmable vacuum operation helps get to the necessary vacuum level in any condition quickly.
- System leak test to identify gross leaks in a system.
- ✓ Charge accuracy within +/- ½ oz.
- Automatic oil drain shows how much oil was removed from the system during service.
- Automatic air purge removes the potential of air accumulating in the internal tank.
- Integrated refrigerant identifier (meets SAE J2927)
- Liquid refrigerant flushing function can flush A/C systems or individual components using liquid refrigerant instead of harsh chemicals.
- Automatic internal tank refill. No stopping to fill the internal tank during service, or before service.
- ✓ 1/4 Color VGA display. Large easy to read graphical display
- On-board printer capable of printing vehicle service report slips to present to customers.

#### SPECIFICATIONS

- ✓ Operating voltage 103-127V, 60Hz AC
- ✓ 100mm, EN837-1 pressure gauges
- Alpha-numeric keypad with service function keys
- 1.5 cfm dual stage vacuum pump
- 1/3 hp hermetic compressor
- ✓ 22 lb. ASME internal storage tank
- USB, SD, and RJ45 I/O ports
- 8 ft. SAE J2888 service hoses with 1234YF high and low side system couplers
- Meets all requirements of SAE J2843



Item # 64

Meets all requirements of SAE J2843.



13-73 © 2013 Bosch Automotive Service Solutions. All rights reserved. Because of ongoing product improvements, we reserve the right to change design, materials, and specifications without notice. Certain kits may require additional cables or adapters. Product shipped may differ from photo(s) shown.

## NEW 1234YJ REFRIGERANT RECYCLERS




## **NEW ...** Model 37860

## Designed to handle the new 1234YJ Refrigerant on 2016 car models

#### Features/Information:

- Can order a 1234YF model outright or a 134a model and convert it over in the future using a conversion kit.
- Makes the shop more money by increasing technician productivity:
- The unit's portable tablet enables the tech to work on another vehicle while monitoring the AC service activity on the first vehicle.
- · Provides a host of technician-friendly features to get the job done faster:
- A large flat work area.



- Hooks and magnets to attach job jacket, hold notes, hold rags, etc.
  - Various trays to hold small components during the repair/service, to hold pens, and to hold small tools.
  - The tablet can be used for traditional internet searching to find parts, access databases, look up manuals, search repair techniques.
  - Ritchie Engineering can remotely access the system to assist in set-up or to provide trouble shooting assistance.
  - · Stable and rugged for any shop
  - Built in the USA and built with Yellow Jacket quality and dependability





## DIESEL EXHAUST FLUID (aka DEF)

# What is DEF & Are you ready to handle it?

The Clean Air Act as passed by Congress mandates cleaner Diesel Emissions. Vehicle and engine manufacturers have developed a technology called, Selective Catalytic Reduction (SCR) for diesel engines. This technology uses Diesel Exhaust Fluid to convert the NOX into harmless nitrogen gas (N2) and water vapor (H2O).

We offer a wide range of true blue DEF dispensing equipment system packages designed specifically to handle DEF. As your DEF volume increases, the true blue system packages can easily be adapted to fit various container sizes and dispensing options.





## **Credit Application for Equipment Financing 12**



## Questions? Call Bill Waddell 888-461-7002

bwaddell@adgequipment.com

LESSEE INFORM	IATION									
Legally Registered	Name:			.Trade/	DBA Name	Primary	Contact			
Physical Address –	( HQ or Exist	ting Street A	Address) City, S	tate, Zip	Code	Phone Nu	Phone Number			
Equipment Locatio	on – (New, If I	Moving or F	Expanding) City,	State, Zip Code Pri			Contact Cell Pho	1e		
Type of Business ProprietorshipPartnershipC-CorporationS-CorporationLLCNon Profit  Do you Own theNature of			State of Incorporation  Business	 (Minimu Or Call	Years in Business  Years Months  (Minimum 2 Years, Under Current Owner, Or Call For New Business Program Quote)  E-mail Address			loyees		
Equipment Location (circle one) YES	S NO									
BUSINESS CHECK		RMATION					<u> </u>			
Name of Bank: PRINCIPAL INFO	Phone		Contact:	СОМРА	bank stat	ful to send the f	irst page of the pas			
Principal First Nam		Last Name		1	Address (Street Ad					
						,,	····, —- <b>F</b> )			
Title % (	Ownership	Home Pho	one #	Cell Ph	none #	Social Sec	Social Security Number			
Principal First Nam	me	Last Name	e	Home Address (Street Address, City, State, Zip)						
Title %	Ownership	Home Pho	ne #	Cell Ph	one #	Social Sec	Social Security Number			
EQUIPMENT INF	FORMATION	(Please fil	ll out known info	ormation	)	<u>L</u>				
Equipment Cost: \$ Estimated Descripti		ade for wo	Are you purchasing additional equipment for your office you would like to lease, such as phones,		Lease Term 24, 36, 48, 60 months (circle)	Expected Delivery Date	Purchase C \$1.00 Other Options Upon Rec	Available		
New Remanufactured Used			computers, furniture, security? Short Availa		Shorter Terms Available Upon Request			•		
DEALER OR SUP	PLIER INFO	RMATION		•						
Dealer:		Contact:		Phone		E-Mail				
By signing below, the unde personal credit profile prov collection of any resultant <b>APPLICATION.</b>	vided by national	credit bureaus i	n considering this app	plication and	d for the purpose of the u	pdate, renewal, or e	extension of credit to th	e applicant or the		
Signature X			Date	Sig	gnature X		Da	te		
g	PLI	EASE			TO 866-	-936-020				

## Have We Got A Combo Deal For You...

**M-924HP** 



Purchase
High Performance
Tire Changer
and
Laser Balancer

**SAVE** \$1,000

Handles Low Profile and Run Flat Tires,
Alloy Rims, Spokes & Clad Wheels....
....Be prepared for any Tire/Wheel combination available

Trade-in your old, tired machine....

SAVE MONEY NOW, MAKE MORE MONEY TOMORROW!

You Can Count On Your Local ADG Representative For Quality Products, Advice & Service!